

# **GATES THERMALPRO ELECTRIC WATER PUMPS**

## **RADIAL FLUX 12-20W PLATFORM**

ThermalPro Radial Flux water pumps are manufactured for durable, worry-free operation for the life of your vehicle. Constructed using only premium materials, we rigorously function and leak test our water pumps and components, like seals and bearings, to ensure optimum performance under intense driving conditions.

| SYSTEM OVERVIEW      |                                    |  |
|----------------------|------------------------------------|--|
| Model                | 12-20W platform                    |  |
| Motor type           | Single-phase brushless Radial Flux |  |
| Motor mass           | >220g                              |  |
| Voltage range        | 12V                                |  |
| Flow rate (I/min)    | <8                                 |  |
| Max. operating speed | <6000 rpm                          |  |
| Control strategy     | PWM                                |  |
| Coolant temperature  | -40°C to 120°C (-40°F to 248°F)    |  |
| Ambient temperature  | -40°C to 135°C (-40°F to 275°F)    |  |
| IP rating            | IP65                               |  |

# **GATES RADIAL FLUX EWP DESIGN:**

### **CHASSIS OR DIRECT MOUNTING**

Flexibility to available package

### **RADIAL COILS**

Silent, reliable, low cost design

#### **CONTROL BOARD**

PWM communication

#### **MODULAR AND SCALABLE**

Creating a "family" architecture to different application requirement



| MOTOR DESIGN                 |                                      |
|------------------------------|--------------------------------------|
| Motor details                | Up to 6 tooth 8 poles                |
| Motor housing material       | Glass reinforced plastic             |
| Volute housing and impeller  | Glass reinforced plastic             |
| Winding type                 | Non-overlap concentrated             |
| Winding material             | Copper or aluminum                   |
| Stator & rotor core material | Electrical steel                     |
| Permanent magnet             | Ferrous                              |
| Load protection              | Anti-reverse connection              |
| Coolant specification        | 50:50 ethylene glycol to water ratio |

| STANDARDS              |   |  |
|------------------------|---|--|
| EMC                    | ISO 11451 / ISO 11452 / ISO 10605 / CISPR25     |  |
| Temperature shock test | DIN EN 60068-2-14                               |  |
| Dust test              | ISO 20653                                       |  |
| Thermal cycle          | IEC 60068-2-14                                  |  |
| Vibration test         | ISO 16750-3 / DIN EN 60068-2-6 / DIN 60068-2-64 |  |
|                        |   |  |

