



DRIVEN BY POSSIBILITY™



PRO1T & PRO-V HYDRAULIC HOSE

PRO™ SERIES - COMPACT HYDRAULIC SOLUTIONS FOR THE FACTORY AND FIELD

Gates PRO Series Pro1T and Pro-V variable pressure hydraulic hoses deliver performance and reliability **to compact minimum bend radii.**

Engineered for less demanding hydraulic applications, our new line of professional-grade hoses are **designed to balance product performance and investment** for everyday uses. All sizes deliver consistent **performance to EN industry specifications.**

We believe operating challenges are made to be overcome. That's why thousands of industrial facilities, global operations and OE manufacturers around the world choose Gates hose and hydraulic systems to power their demanding fluid power applications.

FEATURES + BENEFITS

- Ideal for non-severe, medium-pressure hydraulic applications
- Application-specific design offers reliable performance that gets the job done
- Fully compliant with EN 857 SC
- Manufactured to Gates high-quality professional standards
- Compact design is flexible and light weight for easy handling and fast installation

**STRONG, RELIABLE AND FLEXIBLE.
ENGINEERED TO DELIVER DEPENDABLE,
APPLICATION-SPECIFIC PERFORMANCE.**

GATES PRO SERIES PRO1T AND PRO-V HYDRAULIC HOSE: PROFESSIONAL-GRADE HYDRAULIC HOSE SOLUTIONS

Gates PRO Series Pro1T and Pro-V variable pressure hydraulic hoses are qualified for use with the EX Series couplings to ensure end-to-end performance – providing a broad range of engineered solutions for targeted hydraulic applications.

PRODUCT SPECIFICATIONS

- **TUBE:** Black, oil resistant, synthetic rubber tube.
- **REINFORCEMENT:** Braided high-tensile steel: wire.
- **COVER:** Smooth, black, synthetic rubber. Meets MSHA flame resistance.
- **TEMPERATURE RANGE:** -40 °C to +100 °C (-40 °F to +212 °F).

INDUSTRIES + APPLICATIONS

- Agriculture
- Construction
- Mining
- Manufacturing
- Return Lines
- Low Flex Accessory Lines
- Auxiliary Lines
- Drain Lines

EN 857 1SC



-size	↔		○		⌚		🔥		📏		kg/100m	REF.
	DN	"	"	mm	PSI	MPa	PSI	MPa	mm			
-4	6	1/4	0.49	12.5	3250	22.5	13000	90.0	75	19	4PRO1T	
-5	8	5/16	0.54	13.6	3100	21.5	12400	86.0	85	21	5PRO1T	
-6	10	3/8	0.62	15.8	2600	18.0	10400	72.0	90	28	6PRO1T	
-8	12	1/2	0.75	19.0	2325	16.0	9300	64.0	130	34	8PRO1T	
-10	16	5/8	0.89	22.5	1900	13.0	7600	52.0	150	43	10PRO1T	
-12	19	3/4	1.02	25.9	1525	10.5	6100	42.0	180	50	12PRO1T	
-16	25	1	1.31	33.4	1275	8.8	5100	35.2	230	82	16PRO1T	

EN 857 2SC



-size	↔		○		⌚		🔥		📏		kg/100m	REF.
	DN	"	"	mm	PSI	MPa	PSI	MPa	mm			
-4	6	1/4	0.52	13.1	5800	40.0	23200	160.0	50	25	4PROV	
-5	8	5/16	0.58	14.7	5000	35.0	20000	140.0	55	30	5PROV	
-6	10	3/8	0.65	16.6	4800	33.0	19200	132.0	65	33	6PROV	
-8	12	1/2	0.80	20.3	4000	27.5	16000	110.0	90	46	8PROV	
-10	16	5/8	0.93	23.6	3625	25.0	14500	100.0	100	54	10PROV	
-12	19	3/4	1.08	27.4	3100	21.5	12400	86.0	120	67	12PROV	
-16	25	1	1.39	35.4	2400	16.5	9600	66.0	150	102	16PROV	